

IMTS 2022 SPECIAL EDITION

2022 CATALOG

WORLD CLASS TOOL MEASURING AND MANAGEMENT SOLUTIONS

















PRESETTER COMPA

Meet the Presetter: Hub of Innovation

With 12 presetter and inspection system lines, Omega TMM is the final word in presetting and inspection. Our presetter and shrink set machines proudly manufactured and assembled at our USA world headquarters in Fairport, New York, are the most accurate, reliable and repeatable machines on the market. Omega TMM has evolved from decades of leadership in the tool holder and presetter business, formerly known as Parlec Inc.

"Which presetter is right for my business?"

Here at Omega TMM we use a consultative approach to better understand what solutions are right for you and your business process.



Business operations are different at all facilities and Omega TMM can offer a customized solution that specifically fits your business needs.

- RYAN MELEG. EVP SALES

EGEND

STANDARD



OPTIONAL



NOT AVAILABLE

3 Axis CNC

Universal Power Clamping Spindle

Taper 50 Spindle

Auto Focus

Virtual Control Device

Perfect Set Height Adjustment

RFID Tool Identification

Data Output/ Post Processing

AAIM Profiling Software

Mobile Command Center



ARISON

SOLIS	HELIOS	FORTIS	FORTIS XL	EXACTUS LITE	EXACTUS	EXACTUS XL	EVO	EVO+	
Ø	②			×			×	×	
•	×		•	×	×	×	×	×	
×		×	×	②				⊘	
×	×			×			×	×	
⊘				×			×	×	
⊘				×			×	×	
							×	×	
							×		
Ø				×			×	×	
•							×	X	














SOLIS



There is only 1 option for a high-volume shop that utilizes heat shrink tooling and requires pinpoint accuracy, the SOLIS from Omega TMM.

PERFECT SET LENGTH RODS

Provides users the ability to set tool height to an industry leading +/- 5 microns.

LIQUID COOLED TOOL TRAY

The first machine in the industry to offer a liquid cooled tray to cool your hot tools.

LENGTH VERIFICATION SPINDLE

Eliminates the use of "masterpiece" sets to reduce your cycle time by more than a minute and a half!

C.H.I.I.I.

Contained Hyper Infrigidated Lossy Liquid cooling system for our revolutionary SOLIS machine. Self contained and maintenance free our C.H.I.L.L. automated cooling system can cool your heat shrink tools to working temperature in 60 seconds.



"We engineered the SOLIS with the goal of outperforming all other machines in the industry, not only did we succeed, we have revolutionized the industry!"

- MIKE BERNITT, DIRECTOR **OF OPERATIONS**













SOLIS

SOLIS is the fastest, most reliable, and most accurate heat shrink and measurement combo PERIOD. Through years of engineering and innovation Omega TMM has developed the ultimate machine to meet your high capacity heat shrink and presetting needs. Cutting edge technology, such as a proprietary self-cooling induction coil shrink head, mean SOLIS is built for continuous shrinking 24/7, making this presetter a real workhorse.



- » C.H.I.L.L. automated 60 second tool cooling
- » Perfect Set provides users the ability to set tool height to an industry leading +/- 5 microns
- » Length Verification Spindle for quick serial shrinking of different length and diameter tools with no extra "masterpiece" step required
- » Virtual Control Device for simple ergonomic use
- » Mobile Command Center rolling kiosk
- » Precision Tool Tip Finder
- » Fume extractor to remove all vapors produced from the heated tool
- » A fully integrated heat shrink and presetting unit
- » Up to 7 full CNC axis
- » Serial shrinking of different tool height sand diameters
- » 70x Magnification lens

- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » Holding recognition system
- » Liquid cooled tray for hot cutting tools
- » Micron accurate fine adjust
- » OPTIK user interface suite
- » Cold Source LED Tool Inspection Light
- » Dual 21.5" monitors for tool window and user interface
- » 15" touch screen LVS monitor
- » Automated unshrinking of damaged tools
- » Echo
- » AAIM

SPECIFICATIONS

DIMENSIONS & WEIGHT

» Length: 1854mm (73")» Width: 813mm (32")

» Height: 1930mm (76")

» Average Shipping Weight: 930kg (2050lbs)

MEASURING ENVELOPE

» Height: 600mm» Diameter: 320mm» Snap Gauge: 75mm

UTILITIES

» 120V AC or 220V AC, 50Hz to 63Hz

» 480V AC 3 phase

» Air: 80-110PSI















HELIOS





The HELIOS is the most affordable and well optioned heatshrink/presetting combination on the market. Standard features like 4 axis CNC, tool height setting, liquid chilled cooling collars, and automatic broken tool removal make the HELIOS the market leader in affordable heat shrink technology.

"I'm proud to say Team Omega TMM listened to our customers, doing the impossible in record time in an extraordinary year. Customers will receive top performance from a US based



company and superb reliability at a price point that nobody can measure up in the industry."

- MIKE NUCCITELLI, PRESIDENT + CEO













HELIOS

HELIOS is the most affordable and well optioned heat shrink and presetting combination on the market, HANDS DOWN. Standard features like 5 axis CNC, tool height setting, liquid chilled cooling collars, and automatic broken tool removal make the HELIOS the market leader in affordable heat shrink technology.



- » C.H.I.L.L. automated 60 second tool cooling
- » Perfect Set provides users the ability to set tool height to an industry leading +/- 20 microns (patent pending)
- » No extra "masterpiece" step required
- » Precision Tool Tip Finder to easily find your tool tip
- » Fume extractor to remove all vapors produced from the heated tool
- » A fully integrated heat shrink and presetting unit
- » Up to 5 full CNC axis
- » Serial shrinking of different tool

heights and diameters

- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » Liquid cooled tray for hot cutting tools
- » Micron accurate fine adjust
- » OPTIK user interface suite
- » Cold Source LED Tool Inspection Light
- » Dual 21.5" monitors for tool window and user interface
- » Automated unshrinking of damaged tools

SPECIFICATIONS

DIMENSIONS & WEIGHT

» Length: 1854mm (73")

» Width: 813mm (32")

» Height: 1930mm (76")

» Average Shipping Weight:

930kg (2050lbs)

MEASURING ENVELOPE

» Height: 600mm

» Diameter: 320mm

» Snap Gauge: 75mm

UTILITIES

» 120V AC or 220V AC, 50Hz to 63Hz

» 480V AC 3 phase

» Air: 80-110PSI















FORTIS



FORTIS

With a combined clamping force of over 1,300ft/lbs, the FORTIS Series are the most repeatable measuring machines on the market.



FORTIS PRO

Featuring full 3 axis CNC along with incredible clamping force the FORTIS PRO is an industry leader.



FORTIS XL

The FORTIS-XL can handle heights and diameters up to 1000mm and with a 1000lb spindle capacity it can measure any tool in your arsenal.



FORTIS XL PRO

When measuring large tooling, the full 3 axis cnc on the FORTIS XL PRO makes your job simple, repeatable, and reliable.













FORTIS

With over 1300 ft/lbs of power-clamping spindle force the FORTIS Series are the most repeatable measuring machines on the market.



- » +1,300ft/lbs universal power clamping spindle with interchangeable cartridge system to work with any tool holding type
- » Integrated spindle brake and 360° indexing
- » 1 micron repeatable measuring
- » Shop floor ready, full size freestanding machine
- » Spindle weight capacity of over 200lbs
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light

- » Robust easy to use control interface
- » Instantly finds tool geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » Dual 21.5" monitors for tool window and user interface
- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » 70x Magnification lens

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Overall Width: 1575mm (62")

» **Depth:** 813mm (32")

» Height:

400mm Column (1730mm / 68") 600mm Column (1930mm / 76") 800mm Column (2130mm / 84")

» Average Shipping Weight: 522kg (1150lbs.)

MEASURING DIAMETERS

» 420mm (16.5")

UTILITIES

» 120V AC or 220V AC, 50Hz to 63Hz

» Air: 80-110PSI

OPTIONS

MEASURING LENGTHS

- » 400mm (15.75")
- » 600mm (23.6")
- » 800mm (31.5")

CONTROL SYSTEM OPTIONS

- » OPTIK user interface
- » Autofocus CNC Spindle
- » Manual and automated RFID systems
- » Mazak Cyber Tool and Smooth Tool Management system integration
- » Data output
- » Perfect Set with OPTIK Software

- » Holder recognition system
- » AAIM- tool profile software
- » Virtual control device
- » Echo
- » User management
- » Rolling Kiosk
- » Optional: Environmental Enclosure

UPGRADE TO FORTIS PRO

» System is full 3 axis **CNC** automation















FORTIS XL

The FORTIS-XL can handle heights and diameters up to 1000mm and with a 1000lb spindle capacity it can measure any tool in your arsenal.



- » +1,300ft/lbs universal power clamping spindle with interchangeable cartridge system to work with any tool holding type
- » Integrated spindle brake and 360° indexing
- » Simple to use 3D VCD with programmable smart buttons
- » 1 micron repeatable measuring
- » Shop floor ready, full size freestanding machine
- » Spindle weight capacity of over 1000lbs
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light

- » Robust easy to use control interface
- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » Instantly finds tool geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » Dual 21.5" monitors for tool window and user interface
- » 70x Magnification lens
 - *Shown with optional casters

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Overall Width: 1838mm (72.4")

» **Depth:** 701mm (27.6")

» Height:

600mm Column (1948mm/76.7") 1000 mm Column (2342mm/93.2")

» Average Shipping Weight: 1020 kg (2240 lbs.)

MEASURING DIAMETERS

» 420 mm (16.5")

UTILITIES

- » 120V AC or 220V AC, 50Hz to 63Hz
- » Air: 80-110PSI

OPTIONS

MEASURING LENGTHS

- » 650mm 1000mm Length
- » 650mm 950mm Diameter

CONTROL SYSTEM OPTIONS

- » OPTIK user interface
- » Autofocus CNC Spindle
- » Manual and automated RFID systems
- » Mazak Cyber Tool and Smooth Tool Management system integration
- » Data output

- » Perfect Set automated tool height system
- » Holder recognition system
- » AAIM- tool profile software
- » Echo
- » User management
- » Snap Gauge: 100mm

UPGRADE TO FORTIS XL PRO

» System is full 3 axis CNC automation















EXACTUS







EXACTUS LITE

Easy to use, accurate, and robust. The EXACTUS line can transform your production efficiency from good to world class.

EXACTUS

Accurate, repeatable, and reliable. The EXACTUS has the ability to handle any job you can throw at it with simplicity and ease.

EXACTUS PRO

Featuring 3 axis automation, the EXACTUS PRO removes the element of human error from your process.





With the EXACTUS XL there is no job too big or too heavy with up to 1000mm measuring capability and 650lb spindle capacity.



EXACTUS XL PRO

3 Axis automation along with incredible measuring capabilities the EXACTUS XL PRO will make even the most difficult toll setup simple and precise.













EXACTUS LITE

Need accurate measurements straight from your workbench? The EXACTUS LITE tabletop machine is your answer.



- » Precision ground taper 50 spindle
- » Adapters available for all tool holding types
- » 1 micron repeatable measuring
- » Vacuum clamping
- » Shop floor ready
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light
- » Robust easy to use control interface

- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » Instantly finds tool geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » 21.5" LCD touchscreen control
- » Label printer
- » 70x Magnification lens
 - *Shown with optional workbench

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Overall Width: 748mm (30")

» **Depth:** 527mm (21")

» Height:

400mm Column (890mm/ 35") 600mm Column (1115mm/44") 800mm Column (1315mm/42")

» Average Shipping Weight: 272 kg (600 lbs.)

UTILITIES

» 120V AC or 220V AC, 50Hz to 63Hz

» Air: 80-110PSI

OPTIONS

MEASURING LENGTHS

- » 400mm (15.75")
- » 600mm (23.6")
- » 800mm (31.5")

CONTROL SYSTEM OPTIONS

- » OPTIK user interface
- » Manual RFID systems
- » Mazak Cyber Tool and Smooth Tool Management system integration

- » Data output
- » Single or dual 21.5" monitors
- » User management
- » Document manager
- » Template Tracking

ACCESSORIES AVAILABLE

» Solid Maple Top Workbench















EXACTUS

Easy to use, accurate, and robust. The EXACTUS line can transform your production efficiency from good to world class.



- » Precision ground taper 50 spindle
- » Adapters available for all tool holding types
- » 1 micron repeatable measuring
- » Vacuum clamping
- » Shop floor ready full size freestanding machine
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light
- » Robust easy to use control interface

- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » Instantly finds tool geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » 21.5" LCD touchscreen control
- » Label printer
- » 70x Magnification lens

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Overall Width: 1575mm (62")

» **Depth:** 813mm (32")

» Height:

400mm Column (1730 mm / 68") 600mm Column (1930 mm / 76") 800mm Column (2130 mm / 84")

» Average Shipping Weight:
522kg (1150lbs.)

522kg (1150lbs.)

MEASURING DIAMETERS

» 420 mm (16.5")

UTILITIES

- » 120V AC or 220V AC, 50Hz to 63Hz
- » Air: 80-110PSI

OPTIONS

MEASURING LENGTHS

- » 400mm Column (13.75")
- » 600mm Column (23.6")
- » 800mm Column (31.5")

CONTROL SYSTEM OPTIONS

- » OPTIK user interface
- » Autofocus CNC Spindle
- » Manual and automated RFID systems
- » Mazak Cyber Tool and Smooth Tool Management system integration

- » Data output
- » Perfect Set with OPTIK Software
- » AAIM tool profile software
- » Virtual control device
- » Echo
- » User management

UPGRADE TO FORTIS PRO

» System is full 3 axis CNC automation















EXACTUS XL

Cast iron construction with our proprietary SYMMETRY design, our innovative virtual control device, and multiple spindle options make the EXACTUS-XL the definition of the word "heavyweight".



- » Precision ground taper 50 spindle
- » Integrated spindle brake and 360° indexing
- » Simple to use 3D Virtual Control Device with programmable smart buttons
- » Shop floor ready, full size freestanding machine
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light
- » Robust easy to use control interface
- » Pearlitic cast iron construction with our proprietary SYMMETRY design

- » Instantly finds tool geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » Dual 21.5" monitors for tool window and user interface
- » 70x Magnification lens
 - *Shown with optional casters

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» **Overall Width:** 1838mm (72.4")

» **Depth:** 701mm (27.6")

» Height:

600mm Column (1948 mm/76.7") 1000mm Column (2342mm/93.2")

» Average Shipping Weight: 1020kg (2240lbs.)

UTILITIES

» 120V AC or 220V AC, 50Hz to 63Hz

» **Air:** 80-110PSI

OPTIONS

MEASURING LENGTHS

- » 650mm 1000mm Length
- » 650mm 950mm Diameter

CONTROL SYSTEM OPTIONS

- » OPTIK user interface
- » Autofocus CNC Spindle
- » Manual and automated RFID systems
- » Mazak Cyber Tool and Smooth Tool Management system integration
- » Data output

- » Perfect Set automated tool height system
- » AAIM- tool profile software
- » Taper 60 spindle
- » HSK 125a spindle
- » Echo
- » User management

UPGRADE TO FORTIS XL PRO

» System is full 3 axis CNC automation



















EVO+

"What customers benefit from the new EVO?"

The EVO was designed with the operator in mind. We've made it completely customizable and easy to use, while still providing a ton of features. Whether the customer in new to presetting or has used presetters for year they're going to love the new EVO and EVO+.



- ALEX MADDOX, PRODUCT SPECIALIST

INTRODUCING THE NEWEST PRESTTERS

Launched at IMTS 2022, the EVO and EVO+ are the most accurate, repeatable and reliable entry-level presetters on the market.

Standard features include a cast iron construction, an 10.5" touch screen and a match-ground, 50-taper spindle.

The EVO+ version enables users to communicate tooling offsets directly to their machine tool with the click of a button. Both machines offer the ability to personalize the outside with a custom vinyl wrap offering different logos, with one option being an American flag wrap to protect the machine from the shop floor environment.















EVO

Using the latest software and mechanical technologies, the all-new EVO is the easiest, most accurate entry-level machine, targeted to any industry.



- » Cast iron based construction with proprietary SYMMETRY design
- » Precision match ground taper 50 spindle
- » Integrated spindle brake
- » LED surface inspection light
- » NEW and improved EVO control system with new software
- » 10.5" High-res PixelSense™ touch screen

- » 20x magnification
- » Self-balanced counter weight design that requires no shop air
- » Shop floor ready with rigid steel exterior
- » 1-year parts & labor warranty

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Overall width: 760mm (30")

» **Depth:** 521mm (20.5")

» **Height:** 927mm (36.5")

» Average Shipping Weight: 159kg (350lbs)

MEASURING ENVELOPE

» 400mm (15.75") Height 250mm (10") Diameter

UTILITIES

» 120V AC or 220V AC, 50 Hz to 60 Hz

OPTIONS

ACCESSORIES

- » Label Printer
- » Industrial Grade Maple Bench
- » Custom Vinyl Wrapping
- » UPS Battery Backup

CUSTOMIZABLE DESIGNS

Choose from a selection of available designs or work with our design team to customize an EVO with your own branding & protect from environmental elements.













EVO+

Using the latest software and mechanical technologies, the all-new EVO+ is the easiest, most accurate entry-level machine, capable of electronically transmitting tool measurements to your manufacturing operations.



- » Cast iron based construction with proprietary SYMMETRY design
- » Precision match ground taper 50 spindle
- » Integrated spindle brake
- » LED surface inspection light
- » Precision laser tool tip finder
- » NEW and improved EVO control system with new software

- » 21.5" Touch screen
- » 42x magnification
- » Self-balanced counter weight design that requires no shop air
- » Shop floor ready with rigid steel exterior
- » 1-year parts & labor warranty

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Overall width: 760mm (30")

» **Depth:** 521mm (20.5")

» **Height:** 927mm (36.5")

» Average Shipping Weight: 159kg (350lbs)

MEASURING ENVELOPE

» 400mm (15.75") Height 250mm (10") Diameter

UTILITIES

» 120V AC or 220V AC, 50 Hz to 60 Hz

OPTIONS

ACCESSORIES

- » Label Printer
- » Industrial Grade Maple Bench
- » Custom Vinyl Wrapping
- » UPS Battery Backup

CUSTOMIZABLE DESIGNS

Choose from a selection of available designs or work with our design team to customize an EVO+ with your own branding & protect from environmental elements.















SPECIALTY MACHI

Specialty **Machines**

Omega TMM has created a lineup of industry specific measuring and induction machines to meet the specific needs of our customers. From glass grinding, to metal cutting, to stone grinding, rest assured Omega TMM has your needs covered.



Universal Power Clamping Spindle

Virtual Control Device

RFID Tool Identification

AAIM Profiling Software



NE LINEUP

APEX	MICRO	VERI-GRIND	VERI-GRIND LITE
•	•	Ø	×
•	•		×
	×	•	•
⊘			×
			×
•		•	×
•	⊘		













APEX

Reflection and dirt are the enemies of creating an accurate tool profile. Our APEX machine features a full environmental enclosure with an automated light diffuser to make sure your tools are kept safe from the perils of the shop floor. The APEX can profile all types of tools or grinding wheels for any industry using our AAIM software creating the perfect DXF for comparison or export. Whether it is basic presetting or profiling wheels or form tools the APEX is a world class machine.



- » Fully integrated environmental enclosure with auto-retracting light diffuser
- » AAIM profiling software
- » User management
- » Echo
- » Instantly finds tool geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » Dual 21.5" monitors for tool window and user interface
- » Virtual Control Device
- » 70x Magnification Lens

- » +600lb/ft universal power clamping spindle with interchangeable cartridge system to work with any tool holding type
- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » Integrated spindle brake and 360° indexing
- » 1 micron repeatable measuring
- » Shop floor ready, full size freestanding machine
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light
- » Robust easy to use control interface

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Length: 939.8 mm (37")

» Width: 1168.4mm (46")

» Height: 1828.8mm (72")

» Weight: 475kg (1046lbs)

MEASURING ENVELOPE

- » 600mm Height
- » 420mm Diameter
- » 100mm Snap Gauge

UTILITIES

- » 120V AC or 220V AC, 50Hz to 63Hz
- » Air: 80-110PSI

OPTIONS

- » Holder Recognition System
- » Automated RFID
- » Data output
- » Perfect Set automated tool height system

» Mazak Cyber Tool and **Smooth Tool Management** system integration















MICRO

Developed specifically for micro tools and micro features. With an industry-leading 300x lens, the MICRO presetter can measure even the most microscopic features repeatedly and accurately.

If your process requires the use of micro tooling from endmills and drills to super abrasive grinding tools. The 300x lens on the Omega TMM MICRO will ensure a crisp image with industry leading accuracy to set your tools.



- » Fully integrated environmental enclosure with auto-retracting light diffuser
- » 300x magnification bi-telecentric lensing
- » 600+ lb/ft universal power clamping spindle with interchangeable cartridge system to work with any tool holding type
- » Integrated spindle brake and 360° indexing
- » 1μ or less repeatable measuring
- » Shop floor ready, full size freestanding machine
- » Precision Tool Tip Finder

- » Cold Source LED Tool Inspection Light
- » AAIM Profiling Software
- » ECHO
- » Virtual Control Device
- » Robust easy to use control interface
- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » 21.5" tool window monitor
- » 3-Axis CNC
- » OPTIK User Interface

SPECIFICATIONS

DIMENSIONS AND WEIGHT

» Overall Width: 1575mm (62")

» **Depth:** 813mm (32")

» Height: 600mm Column (1730mm / 68")

» Average Shipping Weight: 522kg (1150lbs.)

MEASURING DIAMETERS

» 420mm (16.5")

UTILITIES

» 120V AC or 220V AC, 50Hz to 63Hz

» Air: 80-110PSI



"There is no other presetting machine available on the market that can come close to the accuracy and repeatability of the Omega TMM MICRO on even your smallest of tooling."

- MIKE BERNITT, DIRECTOR OF OPERATIONS

OPTIONS

CONTROL SYSTEM OPTIONS

- » Manual and automated RFID systems
- » Mazak Cyber Tool and Smooth
- » Tool Management system integration
- » Data output
- » Perfect Set automated tool height system
- » Holding recognition system















VERI-GRIND

The VERI-GRIND is the benchmark for grinding wheel form and offset verification in both the metal cutting and stone grinding industries.



- » Instantly finds tool and wheel geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » Dual 21.5" monitors for tool window and user interface
- » Label printer
- » Precision ground taper 50 spindle
- » Adapters available for all tool holding types
- » 1 micron repeatable measuring

- » Vacuum clamping
- » Pearlitic cast iron construction with our proprietary SYMMETRY design
- » Shop floor ready full size freestanding machine
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light
- » Robust easy to use control interface
- » AAIM profiling software with tolerance banding
- » 70x Magnification lens

SPECIFICATIONS

MEASURING DIMENSIONS

- » 420mm (16.5") Diameter
- » 400mm (15.75") Height

UTILITIES

- » 120V AC or 220V AC, 50Hz to 63Hz
- » Air: 80-110PSI

DIMENSIONS AND WEIGHT

- » **Overall Width:** 1575mm (62")
- » **Depth:** 813mm (32")
- » Average Shipping Weight: 522kg (1150lbs.)

OPTIONS

CONTROL SYSTEM OPTIONS

- » Automated or manual RFID
- » Data output
- » Document manager
- » User management
- » Echo















VERI-GRIND LITE

VERI-GRIND LITE is the cost-effective bench-top solution for grinding wheel verification.



- » Precision ground taper 50 spindle
- » Adapters available for all tool holding types
- » Template tracking to verify wheel forms
- » 1 micron concentricity
- » Vacuum clamping
- » Shop floor ready
- » Precision Tool Tip Finder
- » Cold Source LED Tool Inspection Light
- » Pearlitic cast iron construction with our proprietary SYMMETRY design

- » Robust easy to use control interface
- » Instantly finds tool geometries
- » Theoretical intersection points
- » Fixed or Dynamic cross-hairs
- » 21.5" LCD touchscreen control
- » Label printer
- » 70x Magnification lens
 - *Shown with optional workbench

SPECIFICATIONS

MEASURING DIMENSIONS

- » 420mm (16.5") Diameter
- » 400mm (15.75") Height

UTILITIES

- » 120V AC or 220V AC, 50Hz to 63Hz
- » Air: 80-110PSI

DIMENSIONS AND WEIGHT

- » **Overall Width:** 748mm (30")
- » **Depth:** 527mm (21")
- » Machine Height:

400mm Column (890mm/ 35") 600mm Column (1115mm/44") 800mm Column (1315mm/42")

» Average Shipping Weight: 272kg (600lbs.)

OPTIONS

MEASURING OPTIONS

- » OPTIK user interface
- » Manual RFID systems
- » Data output
- » Single or dual 21.5" monitors

ACCESSORIES AVAILABLE

» Solid Maple Top Workbench















SHRINKSET

Shrink/remove and cool your tools automatically with the press of a button.



- » 480v power supply
- » Oscillating air cooling (SHRINKSET and SHRINKSET LITE)
- » Lightning-fast quench cooling (SHRINKSET Pro)
- » Adapters and stop discs for multiple tool types are included
- » Automated Cooling Cycle

- » Easy to use full color LCD touch-screen display
- » Automated Heat Cycle
- » Manufactured, assembled, and supported in the U.S.A.

ACCESSORIES AVAILABLE

» Solid Maple Top Workbench

SHRINKSET LITE

» Machine Type: Compact Tabletop

» Heating Time: <5 Seconds</p> » Cooling Time: 2 Minutes

» Cooling Type: Oscillating Air

» Tool Size:

Max Length: 280mm/533mm with Ext. (11"/21")

Max Diameter: 3mm-32mm (1/8"-1 1/4")

» Adapters Included: HSK100/63/50/40

CAT50/40/30 Capto C6

SHRINKSET

» Machine Type: Full-Size Tabletop

» **Heating Time:** <5 Seconds » Cooling Time: 2 Minutes

» Cooling Type: Oscillating Air

» Tool Size:

Max Length: 560mm (22")

Max Diameter: 3mm-32mm (1/8"-1 1/4")

» Adapters Included:

HSK100/63/50/40 CAT50/40/30

Capto C6

SHRINKSET PRO

» **Machine Type:** Freestanding Machine

» Heating Time: <5 Seconds</p>

» Cooling Time: 30 Seconds

» Cooling Type: Auto Quench

» Tool Size:

Max Length: 560mm (22")

Max Diameter: 3mm-32mm (1/8"-1 1/4")

» Adapters Included:

HSK100/63/50/40

CAT50/40/30

Capto C6







TOOLINSPECTION MACHINES

Guarantee Tool Quality

The Omega TMM Vue and Vue Lite are the perfect solutions for in process tool inspection for any tool grinder. The ability to quickly and accurately check gash, helical angle, land width and more helps you create a considerably more robust process to guarantee your tools quality.



"Easy to use and amazingly accurate the Omega TMM Vue and Vue Lite are real game changers in the tool grinding industry."

> - ALEX MADDOX, **PRODUCT SPECIALIST**











VUE

The Omega TMM Vue is a simple yet robust machine for the inspection of your cutting tools. With magnification up to 145x and easy measurements of helical angle and land width the Vue is the perfect inspection machine for any tool maker!



- » Ball nose
- » Radii inspection using edge detection
- » Step reamer
- » .DXF file overlay
- » Rake angle inspection using scales
- » Helical angle and land width 0.0030mm tool getting measurements plotting with points
- » Angle measurements plotting with points

- » Measurements found after the points
- » Rotating Axis
- » Creation of Reports
- » Document the Image

ACCESSORIES AVAILABLE

» Solid Maple Top Workbench

ADVANCED SOFTWARE

- » Microscope: 00484-1A 12x optical system
- » Magnification: 12.5x, 20x, 30x, 40x, 50x, 60x, 70x, 80x, 90x, 110x, 120x, 125x, 130x, and 145x
- » **Field of View:** 12.5x = 25mm, 20x = 16.7mm, 30x = 11.6mm, 40x = 8mm, 50x = 6.6mm, 60x = 5.4mm, 70x = 4.55mm, 80x = 4.0mm, 90x = 3.5mm. 110x = 3.0mm. 120x = 2.8mm. 125x = 2.6mm, 130x = 2.5mm, 145x = 2.3mm
- » **Range of Focus:** 36mm (1.437")
- » Camera: 5 megapixel, ½" format USB 3.0 color camera
- » Computer: Dell mini-tower or desktop, i7 quad core processor, 8 GB RAM, 500 GB hard drive. Digital DP 4K video card
- » Monitor: 24" diagonal 3480 x 2160 RES flat panel
- » Operating System: Windows 7, 64 bit; Windows 10, 64 bit
- » Scales: Fagor 1 micron
- » **Light:** Variable Intensity LED work light manufacturers, operating systems and computer components as needed

- 1Realtime Cutting Tool Inspection
- » Language: English, German, Chinese
- » Software Upgrades: Software upgrades are free using "Check for Upgrade" in software File menu, v. 7 only
- » Screen Resolutions: Low = .010mm (.00039") High = .001mm (.000039")
- » **Repeatability:** .005 mm (.0002") at max. magnification
- » Measuring Range: 75mm vertical x 200 mm horizontal (50mm of additional vertical optionally available)

GENERAL INFORMATION

- » Dimensions: 24" wide x 19" deep x 18" high
- » Weight: 140 lbs
- » **Power:** 110V default; 220V optional

WARRANTY

» One year on all parts supplied by Omega TMM at the time of purchase as an upgrade or full system







VUE LITE

Simple and easy-to-use are the two words that come to mind when using the Vue Lite tool inspection machine. With 95x magnification and the most intuitive tool inspection software in the industry the Vue Lite is light-years ahead of its competition.



- » Ball nose
- » Radii inspection using edge detection
- » Step reamer
- » .DXF file overlay
- » Rake angle inspection using scales
- » Helical angle and land width 0.0030mm tool getting measurements plotting with points
- » Angle measurements plotting with points

- » Measurements found after the points
- » Rotating Axis
- » Creation of Reports
- » Document the Image

ACCESSORIES AVAILABLE

» Solid Maple Top Workbench

ADVANCED SOFTWARE

- » **Microscope:** 00464-1A 6X optical system
- » Magnification: 15x, 20x, 30x, 40x, 55x, 75x, 95x2
- » **Field of View:** 15x = 22mm, 20x = 16.5mm, 30x = 11.0mm, 40x = 8mm, 55x = 6.5mm, 75x = 4.2mm, 95x = 3.5mm
- » Camera: 5 mega pixel, ½" format USB 3.0 color camera
- » Range of Focus: 12mm
- » **Computer:** Dell mini-tower or desk top, i7 quad core processor, 8 GB RAM, 500 GB hard drive. Digital DP 4K video card
- » Monitor: 24" diagonal 3840 x 2160 RES flat panel
- » Operating System: Windows 7, 64 bit; Windows 10, 64 bit
- » Scales: Fagor 1 micron
- » **Light:** Variable Intensity LED work light

- » Language: English, German, Chinese
- » **Software:** Software upgrades are free using "Check for Upgrade" in software file menu, v.7 only
- » Measuring Range: 75mm vertical x 200mm horizontal
- » **Repeatability:** .010mm (.0005") at max. magnification

GENERAL INFORMATION:

- » **Dimensions:** 24" wide x 19" deep x 18" high
- » Weight: 140lbs
- » Power: 110V default; 220V optional

WARRANTY

» One year on all parts supplied by Omega TMM at the time of purchase as an upgrade or full system



SOLUTIONS

A Giant Leap Towards Complete Interconnectivity

Matrix 4.0, robotic solutions, automated tool vending, CAM integration, total tool management, and Turn-key custom applications are just a few of the ways Omega TMM can help you gain efficiency and create an interconnected factory. Every Smart Factory solution that is provided by Omega TMM is completely customized to meet and exceed your expectations!

SOLUTIONS MADE EASY.

Feel confident that our decades of experience, from working with Top 100 clients all the way to small startups give you the edge that you are investing in a company who will be with you every step of the way. We know the shop floor well. We work on behalf of you to pull in the right partners who have been vetted and tested throughout the tool management life cycle. Our goal is to simplify the way work gets done and get you the right solution to what you are trying to solve. Remember we know tool measuring since we created it over 40 years ago.







MATRIX 4.0

Matrix 4.0 is the most robust cost-effective solution on the market to move toward secure tooling data management.

The Omega TMM Matrix 4.0 system provides universal direct connectivity to safely upload machine tool offsets with minimal human interaction. Multiple checks and balances provide piece of mind that you have the right tool in the right pocket in the correct machine tool.



ADVANTAGES

- » Universal 2-Way Direct Communication Via Ethernet
 - » Keyboard emulator not required
 - » Works with any CNC machine control
- » Data Transfer Process Control
 - » Mitigates operator error, removes the human element of typing in offsets
 - » Fewer broken tools and non-conforming parts
- » Reliable, secure system that creates repeatable tool management ecosystem
 - » Increase efficiency and uptime
- » Open System Platform compatible with multiple manufacturers
 - » Ability for additional IOs supported
- » Software developed and supported in the USA
 - » Quick response to support your operations

HIGHLIGHTS

- » 2D Matrix Scanning
 - » Powered by Caron Engineering Tool Connect
 - » Full service provided by our team of certified technicians
- » Durable and Shop Floor Ready
 - » Configured to your exact requirements
- » Customized to Your Shop Floor
 - » A no-cost shop floor assessment to identify your individual needs
- » Compatible with ANY Presetter
- » Two-Way Communication





MEASURE TOOL

Capture tool data and print matrix code



SCAN MATRIX CODE

Optional hands-free scanning



PLACE TOOL IN CNC

Ready to use







SOFTWARE

Software Solutions

YOUR GATEWAY TO PERFECTION

All Omega TMM software is designed and written by our in-house Software Team. Our software team has always been involved in everything from product design to working with the service team at a customer site, even custom integrations. We develop our software for the end-users, and in each new update or platform release, user feedback and ease of use is the central pillar.

Our team works right here in the USA, out of our Global Headquarters in Fairport, NY.

User friendly yet robust, our OPTIK software suite is designed for productivity. Intuitive function and an elegant, no-nonsense, user interface make Omega TMM the easiest to use on the market.













FAST USER-FRIENDLY SCALABLE SECURE VIBRANT Optik is designed with flexibility, upgraded performance, and a responsive, customizable user interface.

Optik uses the latest technologies, with modularity of features and a sleek, modernized user interface all on one screen. Easier to train, easier to learn, uniform across different machines.



Capture X, Z, radii and angles in real time



Data is sent to RFID systems and machine controls



Clean and informative reporting



Efficient and accurate built-in routines



Mechanical components move at your fingertips











INTUITIVE & RELIABLE CUSTOMIZABLE ROUTINES

Optik is adaptable to integrate with any third party software. Easy drag & drop features with powerful best in breed tool measuring software across all presetter models.

"Can I upgrade my current software version?"

"Depending on your current Omega TMM presetter, you may be eligible to upgrade. Contact our sales department for a free assessment to see if your hardware is compatible with Optik."

- MIKE BERNITT, DIRECTOR OF OPERATIONS



CONTACT US FOR MORE INFORMATION SALES@OMEGATMM.COM

AUTOMATION-READY TOOL MANAGEMENT

Optik's architecture allows you to quickly develop solutions for automatic, repeatable measuring routines and macros, integrated and adaptable to any of our partners' shop floors.



DESIGNED, DEVELOPED, & SUPPORTED IN-HOUSE

Talk to our in-house software team about all your software questions - they've got solutions.

We are Omega TMM – World-class tool measuring and management solutions, where our passion is your production. Our shop floor management solutions, presetter and shrink set machines, proudly manufactured and assembled at our Fairport, NY world headquarters, are the most accurate, reliable, and repeatable measuring machines on the market. Everything we do is laser-focused on creating an outstanding customer experience. We welcome the chance to assist in making your manufacturing facility truly world class.









MODULES

AAIM

Automated Analysis Inspection and Measurement software allows you to verify profiles and the most difficult forms with ease. Our fully automated imaging software will create a 2+ million point cloud to generate a micron precise DXF for overlay or export. Robust features like tolerance bands, nominal vs. actual comparison, and shadow delete make AAIM your number one choice for all your profiling needs. (3 axis CNC required)

MACRO

The world's only "learning presetter"! Simply turn on the Echo function, measure your tool and Echo will learn your movements, optimize the program, and create your macro. This is hands down the simplest way to program presetting macros on the market. Period. (3 axis CNC required) The Omega TMM Macro module allows users to create automated measuring routines to fit their process and their needs. Our Macro Builder uses an intuitive drag-and-drop canvas to select customizable commands, allowing users to build routines that can be applied to a single tool or an entire class of tooling. A Macro can be fully automated on a Presetter equipped with 3-Axis CNC, or can give step-by-step measurement instructions on a manual machine with an Autofocus spindle.

"Optik is a huge step forward, not just for Omega TMM but for the presetter industry as a whole. Many competitors will try to replicate what we have done but with continued innovation we will always be three steps ahead."

- TIM SHOR, DIRECTOR OF SOFTWARE ENGINEERING



VERI-GRIND SOFTWARE


The VERI-GRIND module and VERI-GRIND machines were created to capture tool profiles and automatically align multiple profiles in a set. Within the module, the cutting profile is captured for one or multiple tools in a set. These profiles are then layered and can be automatically adjusted using the "Best Fit" feature, which will take into account the thickness of material being grinded, and will position each tool to achieve the desired profile. The tool measurements can be printed, posted, or written to the tool via RFID and loaded into the machine center, ready for production.

POST PROCESSOR

The Post Processor in OPTIK allows for one-way communication from the OPTIK database directly to a machine center controller, to update data such as tool offsets and supporting information. The Omega TMM Applications team can write custom post templates to integrate to a machine center that allows for a process that does not depend on users manually typing data into the controller. Mitigating the opportunity for user error results in fewer mistakes like mistyped offset values, while at the same time allowing for the immediate transfer of all information that would alternatively need to be manually entered or updated each time a tool is loaded.

RFID

Omega TMM Presetters can transmit data to an RFID chip either manually or with our fully automated RFID system. When a machine center utilizes RFID to maintain and update tool data and information, transmitting tool offset values and other information from the Presetter to the RFID chip on the tool holder is the best way to input this data. When appropriately equipped, an Omega TMM Presetter can automatically identify a tool in the spindle by reading the RFID tag, immediately run an automatic measuring routine, and then write specific tool data back to the RFID tag with the click of a single button.



Custom Interfaces & 3rd Party Integrations

OPTIK supports a range of integration options with 3rd party providers, which can include RFID hardware, tooling databases, and machine control systems.

Our in-house Software team can design and build custom interfaces for one-off solutions or to meet specific needs. Whether the machine needs to communicate with an automated robot for lights-out operation, or if a shop uses a machine center with a unique control, we can create a custom interface if necessary to provide communication and make the process as efficient as possible.

CONTACT US FOR CUSTOM INTEGRATIONS: SALES@OMEGATMM.COM



ACCESSORIES & U



TAPER 50 ADAPTERS

Adapt your taper 50 machine to work with any type of tool holder.

- » All taper types
- » ABS
- » Big Plus
- » Clamping HSK
- » Clamping Capto
- » Clamping KM
- » VDI



CLAMPING CARTRIDGES

All cartridges are universal clamping giving you 600+ ft/lbs of pull force on every tool.

- » All taper types
- » ABS
- » Big Plus
- » Clamping HSK
- » Clamping Capto
- » Clamping KM
- » VDI



CERTIFIED TEST BARS

- » 50 taper: 50mm diameter 150mm projection
- 50 taper: 50mm diameter 300mm projection
- 50 taper: 50mm diameter450mm projection



ZERO GAUGES

50 taper: 50mm diameter75mm projection



PGRADES



BLUE UNDERGLOW

- » Available on all floor models
- » Dress up your shop by adding a blue glow that will make your Omega TMM the most recognizable machine on the shop floor



WORKBENCH

» Mounting table-top machines

ALL AVAILABLE ACCESSORIES

- » Tool tray
- » Cartridge tray
- » Accessory tray
- » Printer
- » Tabletop
- » Holder Recognition System (HRS)
- » Perfect Set
- » Automated RFID
- » Virtual Control Device (VCD)
- » Measuring Sleeves for SOLIS
- » Mazak Cybertool
- » Mobile Command Kiosk
- » Self-Leveling Casters

CUSTOM VINYL WRAPS

- » Available on all presetter models
- » Choose from a selection of available designs or work with our design team to customize a vinyl wrap with your own branding & protect your machine from environmental elements





FOLLOW US:











©Omega TMM, 2022. All Rights Reserved

*Branded product and company names are trademarks™ or registered® trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them.

SALES

Contact us to learn more about available machines, accessories, software and general questions.

P: 1-844-396-5537 Press 2

E: Sales@omegatmm.com

Find your sales manager by state: www.omegatmm.com/sales

SERVICE DEPARTMENT

Customer service for machinery maintenance and repairs is available by phone, or on-location technicians.

P: 1-844-396-5537 Press 1

E: Service@omegatmm.com

Find Service tips and key contact form: www.omegatmm.com/sales/service

CALIBRATION SCHEDULING

We highly recommend annual calibration service by an Omega TMM service expert. Call to schedule your next calibration:

P: 1-844-396-5537 Press 1

E: Service@omegatmm.com

RESOURCES & PRESETTER TRAINING

Take advantage of additional resources and training videos on your new presetter.

Find useful resources at: www.omegatmm.com/resources-downloads

VIRTUAL EVENTS & DEMOS

Our 'John F. Nuccitelli Center for Customer Excellence' hosts live events covering product demos, technology updates and more! No cost! Schedule one today.

P: 1-844-396-5537

E: Sales@Omegal MM.com

ISO & CALIBRATION CERTIFICATES

Available upon request. Please contact us with your specific needs and our Customer Service team will deliver as needed.

P: 1-844-396-5537 Press 1

E: Service@OmegaTMM.com